

						
	<b>HT503</b>	<b>HT801</b>	<b>HT802</b>	<b>HT812</b>	<b>HT814</b>	<b>HT818</b>
<b>Telephone Interfaces</b>	One FXS Port, One FXO Port	One FXS Port	Two FXS Ports	Two FXS Ports	Four FXS Ports	Eight FXS Ports
<b>Network Interfaces</b>	Two 10/100Mbps Ports	One 10/100Mbps Port	One 10/100Mbps Port	Two 10/100/1000Mbps Ports	Two 10/100/1000Mbps Ports	Two 10/100/1000Mbps Ports
<b>SIP Profiles</b>	Two	Two	Two	Two	Two	Two
<b>Fax Over IP</b>	Yes, T.38 Fax	Yes, T.38 Fax	Yes, T.38 Fax	Yes, T.38 Fax	Yes, T.38 Fax	Yes, T.38 Fax
<b>Security</b>	SIPS/TLS, SRTP, HTTPS	SIPS/TLS, SRTP, HTTPS, AES	SIPS/TLS, SRTP, HTTPS, AES	SIPS/TLS, SRTP, HTTPS, AES	SIPS/TLS, SRTP, HTTPS, AES	SIPS/TLS, SRTP, HTTPS, AES
<b>Audio Conferencing</b>	3-Way	3-Way	3-Way	3-Way	3-Way	3-Way
<b>Zero Config</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Provisioning</b>	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069	HTTP, HTTPS, TFTP, TR-069
<b>NAT Router</b>	Yes	No	No	Yes (100Mbps routing speed)	Yes (100Mbps routing speed)	Yes (100Mbps routing speed)
<b>Short / Long Haul</b>	REN 3: 150 ft on 24 AWG lines	2 Ren: 1km on 24AWG Line	2 Ren: 1km on 24AWG Line	3 Ren: 1km on 24AWG Line	2 Ren: 1km on 24AWG Line	2 Ren: 1km on 24AWG Line
<b>Codecs</b>	G.711, G.723.1, G.729 A/B/E, G.726, iLBC	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS	G.711, G.723.1, G.729 A/B, G.726, iLBC, OPUS
<b>Flash Size</b>	4MB	16MB	16MB	16MB	16MB	128MB
<b>Memory Size</b>	16MB	32MB	32MB	128MB	128MB	256MB
<b>Unique Security Certificate per Unit</b>	No	Yes	Yes	Yes	Yes	Yes
<b>Call Feature Support</b>	Advanced Call Features	Advanced Call Features	Advanced Call Features	Advanced Call Features	Advanced Call Features	Advanced Call Features