


UCM6202
UCM6204
UCM6208
UCM6510

SIP Trunks	50	50	50	50
Users	500	500	800	2000
Concurrent Calls	30	45	100	200
Conference Bridges	3	3	6	8
Conference Attendees	25	25	32	64
FXO/FXS Ports	2 FXS/2 FXO	2 FXS/4 FXO	2 FXS/8 FXO	2 FXS/2 FXO
E1/T1/J1 Interface	No	No	No	Yes - 1 RJ45 Port
Network Interface	Two 10/100/1000 Ports with PoE+	Two 10/100/1000 Ports with PoE+	Two 10/100/1000 Ports with PoE+	Two 10/100/1000 Ports with PoE+
QoS	Layer 3, Layer 2	Layer 3, Layer 2	Layer 3, Layer 2	Layer 3, Layer 2
NAT Router	Yes	Yes	Yes	Yes
Clustering Port	No	No	No	Yes
Redundancy	Redundancy with Second UCM	Redundancy with Second UCM	Redundancy with Second UCM	Redundant Power Supply HA100 High Availability Option
RAM/Flash Memory	1 GB RAM, 8 GB Flash	1 GB RAM, 8 GB Flash	1 GB RAM, 8 GB Flash	1 GB RAM, 32 GB Flash
Processor	Dual Core 1GHz ARM Cortex A9/400Mhz VINETIC A8	Dual Core 1GHz ARM Cortex A9/400Mhz VINETIC A8	Dual Core 1GHz ARM Cortex A9/400Mhz VINETIC A8	Quad Core 1GHz ARM Cortex A9/400Mhz VINETIC A8
Licensing Fees	None	None	None	None
Zero Config	Yes	Yes	Yes	Yes